NOTE:
ALL RIGHTS RESERVED. THIS DRAWING OR ANY PART THEREOF MUST
NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION
OF HIGHLAND TANK.
HIGHLAND TANK SHALL BE RESPONSIBLE ONLY FOR ITEMS INDICATED
DIN THIS FABRICATION DRAWING UNLESS OTHERWISE NOTED. DUSTONER
S RESPONSIBLE FOR VERTIFING CORRECTIVESS OF SIZE / LOCATION
OF FITTINGS; ACCESSORIES & COATINGS SHOWN ON THIS DRAWING

FITTING SCHEDULE

A= 3° ϕ NPT WITH 3° \times 2° NYLON BUSHING B= 5° ρ NPT WITH 5° \times 4° NYLON BUSHING C= 3° ρ NPT WITH 3° \times 2° NYLON BUSHING (FITTING FOR LEAK DETECTION W/ INTERNAL PIPE)

INTERIOR: NONE EXTERIOR: SP-6 BLAST, COAT WITH; CORROCOTE PLUS 15 MILS POLYVEETHANE 70 MLS EINFORCED POLYESTIDR CONSTRUCTION ; FLANGED & DISHED HEADS, LAP WELD ALL EXTERIOR SEAMS ONLY APPROVED LABELS ; U.L. 58, NYC, NYCRR PART 614 STILP, 3 C.L. TANK **©** P.P.Z MONITOR LUG ON S.TJ.P.J MODELS ONLY - 15000 VOLT SPARK TEST PROVIDED AT FACTORY FOR FIDE FIDE MODELS - 35000 VOLT SPARK TEST PROVIDED AT FACTORY FOR F.R.P. WODELS 12" 34" 12" 25" OUTER TANK B ZINC ANDDES REQ. ON S.T.J.P.3 MODELS ONLY INNER TANK (1) 10 # PER HEAD STRIKER PLATES TYP. 111 8 3/16" 9 3/16" END VIEW -10'-8 3/8" APPROX.

ELEVATION

AREO-POWER 103 SMITHTOWN BLVD SMITHTOWN, NY 11787

DRAWING TITLE

GENERAL NOTES

CAPACITY: 1500 CALLONS
TYPE: 1 380 DOUBLE WALL, UNDERGROUND, NY CITY

DOI-TOA

ITPE : I JOB DAUBLE WALL, DINDERSHAMIND, REID.

MATERIAL : MLD CARBON STEEL
TEST : 3D P.S.I. INNER 5 P.S.I. DUTER
NIN. GAUGE OR THICKNESS (PER ULL 0B):
(BASED ON 60° MAX. BURIAL DEPTH)
INNER HEADS : 5/18° CUTER HEADS : 10 GA.
INNER SHELL : 1/4° OUTER SHELL : 10 GA.

NEW YORK CITY 1500 GAL U/G TYPE 1 DW

REVISION DESCRIPTION 7 DATE REV

ALL PROPTS RESERVED. THIS DRAWING OR ANY PART THEREOF NUST NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION OF AREA—POWER UNITIZED FUELER, INC.

DWC NO:1,5K DW1NYCUG

SCALE: 3/8"=1" DWN BY: HT SHEET: 1 DATE: 11 /1 /02